
















**Tipologia / Type of material:**

Gres porcellanatonato smaltato/Glazed porcelain stoneware - Group Bla GL - Annex G - EN 14411

**Destinazione d'uso del materiale/Intended use of the material:**

Piastrelle ceramiche per pavimenti interni ed esterni / Floor tiles for interior and exterior use

FORMATO NOMINALE/NOMINAL SIZE (mm)	<b>710x710x9,5</b>
SERIE/SERIAL NAME	<b>TOUCH</b>
ARTICOLO/ARTICLE	<b>BIANCO -BEIGE -TORTORA -GRIGIO -NERO</b>

	<b>Caratteristiche/Features</b>	<b>Metodo di prova/ Test method</b>	<b>Valori dichiarati/ Declared values</b>
<b>Dimensioni/Dimensions</b> <small>(W = Dimensione di Fabbricazione/Work Size)</small>	Lunghezza e larghezza/Length and width	 UNI EN ISO 10545-2	W ± 0,6 %; max ± 2,0 mm
	Spessore/Thickness	 UNI EN ISO 10545-2	W ± 5 %; max ± 0,5 mm
	Rettilinearità dei lati/Straightness of sides	 UNI EN ISO 10545-2	W ± 0,5 %; max ± 1,5 mm
	Ortogonalità/Rectangularity	 UNI EN ISO 10545-2	W ± 0,5 %; max ± 2,0 mm
	Planarità/Surface flatness	 UNI EN ISO 10545-2	W ± 0,5 %; max ± 2,0 mm
<b>Fisiche/Physical</b>	Assorbimento/Water absorption E <sub>v</sub>	 UNI EN ISO 10545-3	≤ 0,5 %
	Forza di rottura/Breaking strength	 UNI EN ISO 10545-4	≥ 1300 N
	Modulo di rottura/Modulus of rupture	 UNI EN ISO 10545-4	≥ 35 N/mm <sup>2</sup>
	Resistenza abrasione superficiale /Resistance to surface abrasion	 UNI EN ISO 10545-7	NPD
	Resistenza agli sbalzi termici/Thermal Shock resistance	 UNI EN ISO 10545-9	Resistant
Resistenza al gelo/Frost resistance	 UNI EN ISO 10545-12	Resistant	
<b>Chimiche/ Chemical</b>	Scivolosità/Determination of slip resistance	 -	NPD
	Reazione al fuoco/Fire reaction	 -	A1 <sub>fl</sub>
	Resistenza macchie - classe/Stain resistance - class	 UNI EN ISO 10545-14	≥ 4
	Resistenza ai prodotti chimici d'impiego domestico/Resistance to household chemical products	 UNI EN ISO 10545-13	A/B